

No. : XMIN1708005388PS Date : Sep 04, 2017 Page: 1 of 7

CUSTOMER NAME:	JIANGXI ALUTILE BUILDING MATERIALS CO., LTD.
ADDRESS:	NO.1155, 2 ND CHUANGXIN ROAD, STATE HIGH-TECH. INDUSTRY
	DEVELOPMENT ZONE, NANCHANG, JIANGXI, CHINA

Sample Name	:	ALUTILE FIRE-RESISTANCE ALUMINUM COMPOSITE PANEL
Product Specification	:	Thickness 4.0mm
Manufacturer	:	Jiangxi ALUTILE Building Materials Co., Ltd.
Buyer	:	Jiangxi ALUTILE Building Materials Co., Ltd.
Material and Mark	:	Aluminum, Fire-resistance core

Above information and sample(s) was/were submitted and confirmed by the client. SGS, however, assumes no responsibility to verify the accuracy, adequacy and completeness of the sample information provided by client.

SGS Ref. No.	:	SDHL1708017723FB
Date of Receipt	:	Aug 15, 2017
Testing Start Date	:	Aug 15, 2017
Testing End Date	:	Aug 31, 2017
Test result(s)	:	For further details, please refer to the following page(s) (Unless otherwise stated the results shown in this test report refer only to the sample(s) tested)

Signed for SGS-CSTC Standards Technical Services Co., Ltd Xiamen Branch Testing Center

Rocket Chen Authorized signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sge.com/en/Terms-and-Conditions.agr and, for electronic format documents, subject to Terms and Conditions for the Company subject is the terms and Conditions for the Condition the Conditions for the Conditi

No.31 Xianghong Road, Xiang'An Torch Industrial Zone, Xiamen, Fujian Province, China. 361101 t (86-592) 5765857 f (86-592) 5765380 www.sgsgroup.com.cn 中国 ·福建 ·厦门 ·火炬 (翔安) 产业区翔虹路31号 邮编:361101 t (86-592) 5765857 f (86-592) 5765880 e sgs.china@sgs.com



No. : XMIN1708005388PS Date : Sep 04, 2017 Page: 2 of 7

Test Result Summary

Test(s) Requested	Result(s)
EN 13501-1:2007+A1:2009 Fire classification of construction products and	7 1 1
building elements-Part 1: Classification using data from reaction to fire	Classification: B-s1, d0
tests	
Summary:	•

1. For further details, please refer to the following page(s).



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/terms-en-Document.aspx. Attention is drawn to the limitation of liability, indermitication and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein effects the Company's findings at the time of its intervention only and within the limits of context parties to a transaction forexercising all their rights and obligations under the transaction focuments. This document cennot be reproduced except in full, which prior written approval of the Company Ary unauthorized eliteration, forgery or faisification of the content or appearance of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN-Doccheck@gs.com

No.31 Xianghong Road, Xiang'An Torch Industrial Zone, Xiamen, Fujian Province, China. 36 1101 t (86-592) 5765857 f (86-592) 5765380 www.sgsgroup.com.cn 中国 ·福達 •厦门 ·火炬 (翔安) 产业区翔虹路31号 邮编: 36 1101 t (86-592) 5765857 f (86-592) 5765380 e sgs.china@sgs.com



No. : XMIN1708005388PS Date : Sep 04, 2017 Page: 3 of 7

TESTS AND RESULTS

Test Conducted:

This test is conducted as per EN 13501-1:2007+A1:2009 Fire classification of construction products and building elements-Part 1: Classification using data from reaction to fire tests. And the test methods as following:

- 1. EN 13823:2010+A1:2014 Reaction to fire tests for building products-Building products excluding floorings exposed to the thermal attack by a single burning item.
- 2. EN ISO 11925-2:2010 Reaction to fire tests-Ignitability of building products subjected to direct impingement of flame-Part 2: Single-flame source test.

Mounting and fixing (For EN 13823):

The specimen was tested free standing at a distance of at least 80 mm from the backing board. Both wings were clamped at the top and the bottom.

Test Results:

Test method	Parameter	Number of tests	<u>Results</u>
	FIGRA _{0.2MJ} (W/s)		57.6
	THR _{600s} (MJ)		1.5
	SMOGRA (m ² /s ²)		3.8
EN 13823:2010+A1:2014	TSP _{600s} (m ²)	3	17.8
	LFS < edge of specimen	<i>FS</i> < edge of specimen	
	Flaming particles or droplets		No
EN ISO 11925-2:2010	<i>F</i> s ≤ 150 mm	6	Yes
Exposure = 30 s	Ignition of the filter paper	5	No

Remark:

FIGRA-Fire growth rate index used for classification purposes [W/s]

中国•福建•厦门•火炬(翔安)产业区翔虹路31号

For the classes A2 and B, FIGRA_{0.2}MJ

For the classes C and D, $\mathsf{FIGRA}_{0.4}\mathsf{MJ}$

LFS-Lateral flame spread m

THR_{600s}-Total heat release within 600 s MJ



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions of Electronic format documents, at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, at advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's solid the ransaction document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's solid the company and the ransaction forcement. Single company's solid their rights and obligations under the transaction document does not excorerate parties to a transaction form exercising all their rights and obligations under the transaction document. This document does onto excorerate parties to a transaction document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention:To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN-Docenck@gs.com

邮编:361101 t (86-592) 5765857

f (86-592) 5765380

e sgs.china@sgs.com



No. : XMIN1708005388PS Date : Sep 04, 2017 Page: 4 of 7

SMOGRA-Smoke growth rate [m²/s²]

TSP_{600s}-Total smoke production within 600 s m²

Classification and direct field of application:

This classification has been carried out in accordance with EN 13501-1:2007+A1:2009.

Classification:

Fire behaviour		Smoke production			Flaming	droplets
В	_	S	1	,	d	0
		Reaction to f	ire classification	on: B-s1, d0		

Remark:

The classes with their corresponding fire performance are given in Table 1.

Reaction to fire classification is based on the 7-step scale of A1 to F, where A1 is good and F is bad

Statement:

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use.

Warning:

This classification report does not represent type approval or certification of the product.

The test laboratory has, therefore, play no part in sampling the product for the test, although it holds appropriate references to the manufacturer's factory production control that is aimed to be relevant to the samples tested and that will provide for their traceability.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service pr overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format docum subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-Conditions/Terms-end-C e limits a (86-755) 8307

No.31 Xianghong Road, Xiang'An Torch Industrial Zone, Xiamen, Fujian Province, China. 361101 t (86-592) 5765857 f (86-592) 5765380 www.sgsgroup.com.cn e sgs.china@sgs.com 中国•福建•厦门•火炬(翔安)产业区翔虹路31号 邮编:361101 t (86-592) 5765857 f (86-592) 5765380



No. : XMIN1708005388PS Date : Sep 04, 2017 Page: 5 of 7

Table 1 — Classes of reaction to fire performance for construction products excluding floorings and linear pipe thermal insulation products.

Class	Test method(s	6)	Classification criteria	Additional classification
	EN ISO 1182 ^ª and		△ <i>T</i> ≤30°C, and △ <i>m</i> ≤50%, and $t_f=0$ (i.e. no sustained flaming)	-
A1	EN ISO 1716		PCS≤2.0MJ/kg ^ª and PCS≤2.0MJ/kg ^{bc} and PCS≤1.4MJ/m ^{2 d} and PCS≤2.0MJ/kg [°]	-
	EN ISO 1182 ^a or	- and	$\triangle T \le 50^{\circ}$ C, and $\triangle m \le 50^{\circ}$, and $t_{f} \le 20$ s	-
	EN ISO 1716	anu	PCS≤3.0MJ/kg ^a and PCS≤4.0MJ/m ^{2 b} and PCS≤4.0MJ/m ^{2 d} and PCS≤3.0MJ/kg ^e	-
	EN 13823		FIGRA≤120W/s and LFS <edge and<br="" of="" specimen="">THR_{600s}≤7.5MJ</edge>	Smoke production ^f and Flaming droplets/particles ^g
В	EN 13823 a	and	FIGRA≤120W/s and LFS <edge and<br="" of="" specimen="">THR600s≤7.5MJ</edge>	Smoke production ^f and Flaming droplets/particles ^g
	EN ISO 11925-2 ⁱ Exposure =30s		Fs≤150mm within 60 s	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent's intervention only and within the limits of except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN_Doceheck@sgs.com

中国•福建•厦门•火炬(翔安)产业区翔虹路31号

邮编:361101 t (86-592) 5765857 f (86-592) 5765380 e sgs.china@sgs.com Member of the SGS Group (SGS SA)



No. : XMIN1708005388PS Date : Sep 04, 2017 Page: 6 of 7

Class	Test method(s)	Classification criteria	Additional classification
С	EN 13823 and	FIGRA≤250W/s and LFS <edge and<br="" of="" specimen="">THR600s≤15MJ</edge>	Smoke production ^f and Flaming droplets/particles ^g
	EN ISO 11925-2 ⁱ Exposure=30s	Fs≤150mm within 60 s	
D	EN 13823 and	FIGRA≤750W/s	Smoke production ^f and Flaming droplets/particles ^g
	EN ISO 11925-2 ⁱ Exposure=30s	Fs≤150mm within 60 s	
E	EN ISO 11925-2 ⁱ Exposure =15s	Fs≤150mm within 20 s	flaming droplets/particles ^h
F	No performance determined	1	

Note:

^a For homogeneous products and substantial components of non-homogeneous products.

^b For any external non-substantial component of non-homogeneous products.

^c Alternatively, any external non-substantial component having a PCS \leq 2,0 MJ/m², provided that the product satisfies the following criteria of EN 13823: FIGRA \leq 20 W/s, and LFS < edge of specimen, and THR_{600s} \leq 4,0 MJ, and s1, and d0.

^d For any internal non-substantial component of non-homogeneous products.

^e For the product as a whole.

^f In the last phase of the development of the test procedure, modifications of the smoke measurement system have been introduced, the effect of which needs further investigation. This may result in a modification of the limit values and/or parameters for the evaluation of the smoke production. $s1 = SMOGRA \le 30m^2/s^2$ and $TSP_{600s} \le 50m^2$; $s2 = SMOGRA \le 180m^2/s^2$ and $TSP_{600s} \le 200m^2$; s3 = not s1 or s2

^g d0 = No flaming droplets/ particles in EN 13823 within 600 s;

d1 = no flaming droplets/ particles persisting longer than 10 s in EN 13823 within 600 s;

d2 = not d0 or d1.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits to Client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forger or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fulles extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention.To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443.or remail: CN.Doccheck@sac.com
No.31 Xianghong Road, Xiang'An Torch Industrial Zone, Xianen, Fujian Province, China. 36 1101 t (86-592) 5765857 f (86-592) 5765380 www.sgsgroup.com.cn
http://acgai.mg/in/g/in/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/acgai/ac



No. : XMIN1708005388PS Date : Sep 04, 2017 Page: 7 of 7


Ignition of the paper in EN ISO 11925-2 results in a d2 classification.

^h Pass = no ignition of the paper (no classification);

Fail = ignition of the paper (d2 classification).

ⁱ Under conditions of surface flame attack and, if appropriate to the end-use application of the product, edge flame attack.

Note: The above test was carried out by SGS-CSTC Standards Technical Services Co., Ltd. Shunde Branch.



SAMPLE INFORMATION AND PICTURES

******** End of report*******



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-C

No.31 Xiangnong Koad, XiangAn forch industrial Zone, Xiamen, Fujian Province, China. 36 11 01 t (86-592) 5765857 f (86-592) 5765380 www.sgsgroup.com.cn 中国•福建•厦门•火炬(翔安)产业区翔虹路31号 邮编:361101 t (86-592) 5765857 f (86-592) 5765380 e sgs.china@sgs.com